



Cling – The LLVM-based Interpreter

Vassil Vassilev

Why Do We Need Cling?



Cling's advantages:

- ❖ Full C++ support
 - ❖ STL + templates
 - ❖ Path to C++0x
- ❖ Planned massive reduction of dictionaries
- ❖ Easier and smoother transition between interpreted and compiled code
- ❖ Easy maintenance

What Is Cling?



- ❖ An interpreter – looks like an interpreter and behaves like an interpreter
Cling follows the read-evaluate-print-loop (repl) concept.
- ❖ More than interpreter – built on top of a compiler (clang) and compiler framework (LLVM)
Contains interpreter parts and compiler parts. More of an interactive compiler or an interactive compiler interface for clang

What Cling Depends On?



❖ LLVM

“The LLVM Project is a collection of modular and reusable compiler and toolchain technologies...”

- ❖ More than 120 active contributors

Apple, ARM, Google, Qualcomm, QuIC, NVidia, AMD and more

- ❖ ~250 commits/week

❖ Clang

“The goal of the Clang project is to create a new C, C++, Objective C and Objective C++ front-end for the LLVM compiler.”

- ❖ More than 100 active contributors

Apple, ARM, AMD and more

- ❖ ~150 commits/week

Cling's Codebase



LLVM – 430K SLOC*

Clang – 333K SLOC*


Cling – 7K SLOC*

Other ROOT – 1400K SLOC*

CINT+Reflex – 230K SLOC*


Cling – 7K SLOC*

Cling's Codebase



■ LLVM
■ Clang
■ Cling

Cling's Codebase



■ ROOT
■ CINT
■ Cling

* By 12.10.2011. No testsuites included. C and C++ only.
Credits: generated using David A. Wheeler's 'SLOCCount'

Additional Features



- ❖ Just-in-time compiler (JIT)
- ❖ Extra platform support
- ❖ World class performance and optimizations
- ❖ OpenCL
- ❖ Expressive diagnostics
- ❖ ...

Expressive Diagnostics



❖ Column numbers and caret diagnostics

CaretDiagnostics.C:4:13: warning: '*' specified field precision is missing a matching 'int' argument

```
printf("%.~*d");  
~~~~^~
```

❖ Range highlighting

RangeHighlight.C:14:39: error: invalid operands to binary expression ('int' and 'A')

```
return y + func(y ? ((SomeA.X + 40) + SomeA) / 42 + SomeA.X : SomeA.X);  
~~~~~ ^ ~~~~~~
```

❖ Fix-it hints

FixItHints.C:7:27: warning: use of GNU old-style field designator extension

```
struct point origin = { x: 0.0, y: 0.0 };  
^~  
.x =
```

Improving Cling Step-By-Step



Cling prototype in 2010:

- ❖ Shortcomings of the existing prototype were analyzed

Source-to-source manipulations, variable initializers not managed correctly, redundant re-parsing, low efficiency, ...

- ❖ Redesign almost from scratch
- ❖ Resulted in complete rewrite

Advantages of the New Design



- ❖ Rely on the compiler libraries where possible instead of custom implementations

Reduces the maintenance load. If the implementation is not too specific and makes sense for a compiler we prefer putting it into the compiler codebase and delegate the maintenance...

- ❖ More language independent

The necessary code injections and rewrites are directly in the internal structures of the underlying compiler

- ❖ Stability

The new design enables the implementation of stable error recovery

- ❖ Better performance

Re-parsing only in very few cases

Challenges



- ❖ How to combine incompatible concepts like compilation and interpretation

Many tasks that are trivial for an interpreter become a nightmare for a compiler.

- ❖ How to make it user-friendly

First step should be to adopt the successful usability extensions from CINT.

Challenges



How to make it user-friendly

First step should be to adopt the successful usability extensions from CINT.

❖ Value printer

The interactive mode obeys the repl concept and there should be easy, interactive and user-extensible access to types and values

❖ Expressions and statements

CINT-specific C++ extension improving the user interaction with the interpreter from the terminal...

```
[cling]$ sin(1)  
(double const) 0.841471
```

```
void wrapper() {  
    sin(1);  
}
```

Expressions and Statements



- ❖ Wrap the input
- ❖ Scan for declarations
- ❖ Extract the declarations one level up, as global declarations

```
[cling]$ int i = 12; printf("%d\n", i);  
[cling]$ printf ("%f\n", sin(i));
```

```
int i = 12;  
  
void wrapper1() {  
    int i = 12;  
    printf("%d\n", i);  
}  
  
void wrapper2() {  
    printf("%f\n", sin(i));  
}
```

Challenges



How to combine incompatible concepts like compilation and interpretation

Many tasks that are trivial for an interpreter become a nightmare for a compiler.

❖ Initialization of global variables

Cling depends on global variables, which need to be initialized. However, the global variables continue to be added (potentially) with every input line...

❖ Error recovery

Even though the user has typed wrong input at the prompt cling must survive, i.e issue an error and continue to work...

❖ Late binding

Cling needs to provide a way for symbols unavailable at compile-time a second chance to be provided at runtime...

Error Recovery



- ❖ Filled input-by-input from the command line
- ❖ Incorrect inputs must be discarded as a whole

```
***** Welcome to the cling prototype! *****
* Type C code and press enter to run it *
* Type .q, exit or ctrl+D to quit      *
*****
[cling]$ int i; error_here; int j;
input_line_5:2:9: error: use of undeclared identifier 'error_here'
    int i; error_here; int j;
               ^
[cling]$ i
input_line_6:2:2: error: use of undeclared identifier 'i'
    i
    ^
[cling]$ 
```

Late Binding



- ✓ Defined in the root file

```
{  
    TFile F;  
    if (is_day_of_month_even())  
        F.setName("even.root");  
    else  
        F.setName("odd.root");  
    F.Open();  
    hist->Draw();  
    hist->Fill(1.5);  
    hist->SetFillColor(46);  
}  
hist->Draw();
```

- ✗ The root file is gone.
Issue an error.

- + Opens a dynamic scope. It tells the compiler that **cling** will take over the resolution of possible **unknown symbols**

Late Binding



```
{  
    TFile F;  
    if (is_day_of_month_even())  
        F.setName("even.root");  
    else  
        F.setName("odd.root");  
    F.Open();  
    gCling->EvaluateT<void>("hist->Draw()", ...);  
    ...  
}  
hist->Draw();
```

- ❖ Tell the compiler the symbol will be resolved at runtime
- ❖ Wrap it into valid C++ code
- ❖ Partially recompile at runtime

Challenges



❖ Error recovery

Even though the user has typed wrong input at the prompt cling must survive, i.e. issue an error and continue to work...

❖ Initialization of global variables

Cling depends on global variables, which need to be initialized. However, the global variables continue to be added (potentially) with every input line...

❖ Late binding

Cling needs to provide a way for symbols unavailable at compile-time a second chance to be provided at runtime...

❖ Value printer

The interactive mode obeys the repl concept and there should be way of easy print value and type of expression in a user-extensible way...

❖ Expressions and statements

CINT-specific C++ extension improving the user interaction with the interpreter from the terminal...

Dictionaries




- ❖ No reflection information in C++

There is no way a C++ interpreter could know what are the detailed contents of a compiled program

- ❖ CINT and Reflex dictionaries:

- ❖ Take large fraction of libraries
- ❖ Multiple copies of the dictionary data in the memory



Dictionaries in Cling



- ❖ Now the compiler is an interpreter as well!
- ❖ JIT enables native calls into libraries
- ❖ Query the reflection data from compiler libraries
- ❖ Compiled dictionaries should be no longer needed
 - ❖ Middle term: Everything but ClassDef goes away!
 - ❖ Long term: No dictionaries at all

Library Calls in Cling



- ❖ Load the lib
- ❖ #include the header containing the function definition
- ❖ Make the call

```
*****  
[cling]$ .L libz.so  
[cling]$ #include "zlib.h"  
[cling]$ zlibVersion()  
(const char * const) "1.2.3.3"  
[cling]$ █
```

Cling @ the LLVM Community



- ❖ On 25.07.2011 cling was announced on clang's mailing list as a working C++ interpreter
- ❖ People were thrilled and enthusiastic about it
- ❖ Lots of excellent comment and suggestions

The Road Ahead



PCH

Threading

Code Unloading

Integration into ROOT

Integration into ROOT



Ongoing and continuous process that needs:

- ❖ Experience with ROOT
- ❖ Knowledge about cling and clang interfaces

Future: Code Unloading



```
[cling]$ .L Calculator.h
[cling]$ Calculator calc;
[cling]$ calc.Add(3, 1)
[cling]$ 2
[cling]$ .U Calculator.h
[cling]$ .L Calculator.h
[cling]$ Calculator calc;
[cling]$ calc.Add(3, 1)
[cling]$ 4
```

```
// Calculator.h
class Calculator {
    int Add(int a, int b) {
        return a - b;
    }
    ...
};
```

```
// Calculator.h
class Calculator {
    int Add(int a, int b) {
        return a + b;
    }
    ...
};
```

Future: Code Unloading



- ❖ **Fundamental requirement for ROOT**
This is what drives the rapid development in ROOT...
- ❖ **Extremely difficult for a compiler**
Teaching an elephant to dance...
- ❖ **Requires in-depth knowledge of clang internals**
Different phases in the compiler, advanced AST manipulations, inter-procedural analysis, knowledge about LLVM intermediate representation (bitcode), JIT internals, bitcode recompilation...
- ❖ **Thinking out-of-the-box**
Not often seen problem needs novel way of understanding the compiler libraries...
- ❖ **We know how to do it!**
Watermarks, dependency analysis, annotation of the corresponding bitcode, generated for the high-level internal structures,...

Cling in ROOT



- ❖ Lots of interest from experiments and physicists
- ❖ The prototype will be included in the source package of ROOT (the November release)
- ❖ The prototype will be an optional interpreter for ROOT

Demo:

C  N G

Thank you!

Backup slides

Pre-Compiled Headers



Carefully crafted data structures designed to improve translator's performance:

- ❖ Reduce lexical, syntax and semantic analysis
- ❖ Loaded “lazily” on demand

Pre-Compiled Headers



Design advantages:

- ❖ Loading PCH is significantly faster than re-parsing
- ❖ Minimize the cost of reading
- ❖ Read times don't depend on PCH size
- ❖ Cost of generating PCH isn't large

